

## Wood Chic Premium Designer Flooring (Specification Data)

### FLOORING PROPERTIES & PACKAGING

<b>Construction Extruded Core with Pre-Attached Underlayment:</b>	Rigid Core 4.5mm Thick + 1mm IXPE Pad
<b>Collection:</b>	Wood Chic Designer Series
<b>Use:</b>	Commercial & Residential
<b>Size:</b>	9.13" Width X 60" Length (232mm X 1524mm)
<b>Installation Method:</b>	i4F Drop & Lock
<b>Certification:</b>	FloorScore certified by SCS Global Services
<b>Wear Layer:</b>	20mil (0.5mm)
<b>Edge Detail:</b>	Painted Micro-Bevel
<b>Emboss:</b>	Natural Wood Texture
<b>Gauge:</b>	4.5mm Rigid Core + 1mm IXPE Attached Pad = 5.5mm Total Thickness
<b>Planks/Case:</b>	8
<b>Coverage/Each Plank:</b>	3.81 Sq. Ft. (0.354 Sq. Meters)
<b>Coverage/Case:</b>	30.45 Sq. Ft. (2.8289 Sq. Meters)
<b>Coverage/Pallet:</b>	48 Cases/Pallet (1461.6 Sq. Ft. / 135.79 Sq. Meters)
<b>Limited Warranty:</b>	Limited Lifetime Residential / 20-Year Limited Commercial

### STANDARDS – SAFETY & PERFORMANCE

Standard	Description	Requirements	Results
ASTM E648	Critical Radiant Flux (Radiant Panel)	Class I: $\geq 0.45$ W/cm <sup>2</sup>	Surpasses Requirements <sup>1</sup>
ASTM E662	Smoke Density	Flaming & Non-Flaming $\leq 450$	Surpasses Requirements <sup>2</sup>

CDPH/EHLB, Standard Method v1.2	VOCs/TVOCs, Formaldehyde	Refer to Standard	Surpasses Requirements
ASTM F963	Heavy Metals	Refer to Standard	Surpasses Requirements
ASTM D7823 / CPSC-CH-C1001-09.3	Phthalates	Refer to CPSIA <sup>3</sup>	Surpasses Requirements
ASTM D2047	Coefficient of Friction / Slip Resistance	N/A (No Official Requirements)	≥0.6 (Dry)

## STANDARDS – SOUND

Standard	Description	Requirements		Results
ASTM E90 & ASTM E413	Airborne Sound Transmission Loss of Building Partitions and Elements (STC / Sound Transmission Class)	6" Concrete Slab	STC ≥ 50	STC 56 (Surpasses Requirements)
		6" Concrete Slab + Drop-Ceiling	STC ≥ 50	STC 59 (Surpasses Requirements)
ASTM E492 & ASTM E989	Impact Sound Transmission Through Floor-Ceiling Assemblies (IIC / Impact Insulation Class)	6" Concrete Slab	IIC ≥ 50	IIC 57 (Surpasses Requirements)

## STANDARDS – MANUFACTURING & USAGE (ASTM F3261)


Standard	Description	Requirements	Results
ISO 24337	Size	Tolerance - Width of 9.13" (232mm) ±0.008" (±0.20mm) Tolerance - Length of 60" (1524mm) ±0.020" (±0.5mm)	Surpasses Requirements
ASTM F2421	Squareness	≤0.010" (0.25mm)	Surpasses Requirements
ASTM F387	Thickness	With Foam Back Layer Tolerance: ±0.008" (0.2mm) vs. Specified Minimum: 0.080" (2.0mm)	Surpasses Requirements
ISO 24337	Flatness	Max. Values - Width of 9.13" (180mm) Fw ±0.008" (0.2mm) Fl concave ≤ 0.15%; Fl convex ≤ 0.20%	Surpasses Requirements

ISO 24337	Openings	Average (OAvg) $\leq$ 0.004" (0.1mm) Maximum (OM) $\leq$ 0.008" (0.2mm)	Surpasses Requirements
ISO 24337	Ledging	Average (HAvg) $\leq$ 0.004" (0.1mm) Maximum (HM) $\leq$ 0.006" (0.15mm)	Surpasses Requirements
ASTM F1914	Residual Indentation	Average: $\leq$ 0.007" (0.18mm)	Surpasses Requirements
ASTM F1914	Surface Integrity	No puncture through wear layer / décor into rigid core	Surpasses Requirements
ISO 23999	Dimensional Stability	$\leq$ 0.25% / lineal ft. (305 mm)	Surpasses Requirements
ISO 23999	Curling	$\leq$ 0.080" (2.0mm)	Surpasses Requirements
ASTM F925	Chemical Resistance	No more than "Slight Change"	Surpasses Requirements
ASTM F1514	Resistance to Heat	Average $\Delta E < 8.0$	Surpasses Requirements
ASTM F1515	Resistance to Light	Average $\Delta E < 8.0$	Surpasses Requirements
ASTM F970	Static Load	No Official Requirements (Wear Layer < 20mil)	$\leq$ 0.005" (0.13mm), 250psi


## Footnotes

- ASTM E648 - Critical Radiant Flux (Radiant Panel): Passes Requirements for Class I per International Building Code (IBC) 2018 & NFPA 101 Life Safety Code.
- ASTM E662 - Smoke Density: 450 is the limit established by many state, county, and/or local building and/or fire codes, but is not set as a limit for (resilient) flooring products nationwide. Thus, Smoke Density requirements for flooring products may vary from jurisdiction to jurisdiction. Consult your building inspector / fire marshal to learn more.
- CPSIA = Consumer Product Safety Improvement Act.

## Recommend Installation Options:



Ashlar



Stagger