


WoodChic Premium Designer Flooring (Specification Data)**FLOORING PROPERTIES & PACKAGING**

Type of Construction:	Commercial Grade Loose Lay Luxury Vinyl Tile
Collection:	WoodChic Designer Series
Use:	Commercial
Size:	9" Width X 60" Length (228.6mm X 1524mm)
Installation Method:	Glue Down
Certification:	FloorScore certified by SCS Global Services
Wear Layer:	20mil (0.5mm)
Edge Detail:	Beveled Edge
Emboss:	Natural Wood Texture
Gauge:	5mm Total Thickness
Planks/Case:	6
Coverage/Each Plank:	3.75 Sq. Ft. (0.348 Sq. Meters)
Coverage/Case:	22.6 Sq. Ft. (2.0995 Sq. Meters)
Coverage/Pallet:	48 Cases/Pallet (1084.8 Sq. Ft. / 100.78 Sq. Meters)
Warranty:	20-Year Limited Commercial


STANDARDS

Standard	Feature	Performance	
		9 in*60 in*0.5mm	7.25 in*60 in*0.5mm
ASTM F970	Static Load	Passes - 1000 psi	Passes - 1000 psi
ASTM F2199	Dimensional Stability	Passes	Passes
ASTM F1914	Residual Indentation	Passes	Passes
ASTM F1514	Resistance to Heat	Passes - less than 8.0 Delta E.	Passes - less than 8.0 Delta E.
ASTM F1515	Resistance to Light	Passes - less than 8.0 Delta E.	Passes - less than 8.0 Delta E.
ASTM F925	Resistance to Chemicals	Passes - no change	Passes - no change
ASTM E648	Critical Radiant Flux	Passes - >0.45 watts/cm ² , Class 1	Passes - >0.45 watts/cm ² , Class 1
ASTM D2047	Coefficient of Friction, Slip Resistance	Meets SCOF for ADA walking surfaces	
ASTM F410	Wear Layer	Passes	Passes
ASTM D4060	Abrasion Resistance	Passes	Passes
ASTM D7027	Hoffman Scratch	Passes	Passes
EN 16094	Micro-Scratch Resistance (A & B)	Passes	Passes


Recommend Installation Options:



Ashlar



Stagger



Random